



LAIRD BROS (*FORFAR*) LTD

MEDIUM-DENSE FOUNDATION BLOCK

Laird Medium Dense Foundation block is manufactured to BS EN 771-3 at our block plant in Forfar making it possible for split load deliveries. The blocks are within the 20kg one man manual handling limits and are designed for being used below DPC.

Applying this block to your foundation would allow cost savings due to; no need for inner and outer leaves, no cavity fill (no risk of collapsed cavity), no wall ties, with productivity being approximately halved compared to normal cavity construction. The 300mm wide dimension can accommodate a cavity up to 100mm wide, with Lunacrete 100mm blocks on the outer and inner skin, or any timber frame construction.

TECHNICAL INFORMATION

FOUNDATION BLOCK	DENSITY KG/M3	APPROX WEIGHT KG	SHRINKAGE	PER PACK	MORTAR	STRENGTH
MEDIUM DENSE FOUND BLOCKS 440X100X300mm	1500	20	<0.08%	33	REFER BS 5628	7.3N/mm ²
MEDIUM DENSE FOUND BLOCKS *440X100X275mm	1500	18	<0.08%	33	REFER BS 5628	7.3N/mm ²

*MADE TO ORDER

TO ORDER OR FOR MORE INFORMATION PLEASE CONTACT-

OLD BRECHIN RD
LUNANHEAD
FORFAR
DD8 3NQ

TEL 01307 466577
FAX 01307 468642

www.lairdbros.co.uk

All Laird Bros (Ltd) products are manufactured and sold under our Terms & Conditions of sale