

STRATHMORE PAVING LAIRD

Product Datasheet

Features and Benefits

- Close fitting joints and small chamfer allow for a neat spacious appearance. Perfect for children's push toys, roller blades and prams. Also ideal for wheelchairs
- Superb colour definition with German (Lanxess) iron oxide long lasting pigments
- Enhanced durability utilising the most modern German manufacturing technology
- Reduced efflorescence
- Combines a superb smooth finish with impressive slip resistance attributes affording a more professional, yet safer paver
- Product manufactured by a Scottish independent, manufacturing & quarrying in Scotland, negating shipping & reducing road miles, making the actual carbon footprint incomparably lower than the alternatives.

Product Specifications	
Product type	Concrete Paving Block
Manufacturing process	Hydraulically pressed
Manufactured to	BS EN 1338:2003
Installed to	BS 7533-3:2005
Strength	>3.6MPa
Slip/Skid resistance	>70 USRV (extremely low)
Chamfer	Pencil line chamfer
Surface layer	Higher intensity of pigment and cement on the wearing course
Efflorescence	Products placed in a climate controlled curing chamber to minimise its occurrence & severity
Recyclable	100% can be recycled
Application	Domestic, commercial & industrial

product	size (mm)	colours manufactured	m2/pack	m2/slice	no./pack	no./m2	weight/pack (kg)	m2/artic delivery
strathmore 50mm	210 x 175 x 50	autumn leaves, grey, charcoal, scottish heather, bracken & traditional brindle	12.44	1.77	336	27	1,400	273.68

Non stock item colours can be made to order based on minimum quantities and agreement by sales team.