

Cobble Paving

LAIRD

Product Datasheet

Features and Benefits

- Cobble has a distressed aged look that offers both elegance and a timeless form
- Superb colour definition with German (Lanxess) iron oxide long lasting pigments
- Enhanced durability utilising the most modern German manufacturing technology
- Reduced efflorescence
- Combines a superb smooth texture, yet an aged cobbled appearance with impressive slip resistance attributes affording a more professional, yet safer paver
- Product manufactured by a Scottish independent, manufacturing & quarrying in Scotland, negating shipping & reducing road miles, making the actual carbon footprint incomparably lower than the alternatives.

Product Specifications	
Product type	Concrete Paving Block (Cobble)
Manufacturing process	Hydraulically pressed
Manufactured to	BS EN 1338:2003
Installed to	BS 7533-3:2005
Strength	>3.6MPa
Slip/Skid resistance	>70 USRV (extremely low)
Surface layer	Higher intensity of pigment and cement on the wearing course
Efflorescence	Products placed in a climate controlled curing chamber to minimise its occurrence & severity
Recyclable	100% can be recycled
Application	Domestic, commercial & industrial

product	size (mm)	colours manufactured	m2/pack	m2/slice	no./pack	no./m2	weight/pack (kg)	m2/artic delivery
cobble	240 x 160 x 50	brindle, charcoal, burnt ochre, nordic, scottish heather & bracken	11.54	2.3	300	26	1,400	253.88
cobble	160 x 160 x 50	brindle, charcoal, burnt ochre, nordic, scottish heather & bracken	10.77	1.54	420	39	1,400	236.94
cobble	120 x 160 x 50	brindle, charcoal, burnt ochre, nordic, scottish heather & bracken	11.54	1.15	600	52	1,400	253.88

Other colours can be made to order, but based on large quantities.

Visit www.lairdbros.co.uk or call us on 01307 466577