

RECTANGULAR PAVING LAIRD

Product Datasheet

Features and Benefits

- Rectangular profile allows for distinct patterns including herringbone, stretcher bond and basket weave
- Superb colour definition with German (Lanxess) iron oxide long lasting pigments
- Enhanced durability utilising the most modern German manufacturing technology
- Reduced efflorescence
- Combines a superb smooth finish with impressive slip resistance attributes affording a more professional, yet safer paver
- Product manufactured by a Scottish independent, manufacturing & quarrying in Scotland, negating shipping & reducing road miles, making the actual carbon footprint incomparably lower than the alternatives.

Product Specifications	
Product type	Concrete Paving Block
Manufacturing process	Hydraulically pressed
Manufactured to	BS EN 1338:2003
Installed to	BS 7533-3:2005
Strength	>3.6MPa
Slip/Skid resistance	>70 USRV (extremely low)
Chamfer	Pencil line chamfer
Surface layer	Higher intensity of pigment and cement on the wearing course
Efflorescence	Products placed in a climate controlled curing chamber to minimise its occurrence & severity
Recyclable	100% can be recycled
Application	Domestic, commercial & industrial

product	size (mm)	colours manufactured	m2/pack	m2/slice	no./pack	no./m2	weight/pack (kg)	m2/ artic delivery
rectangular 50mm	200 x 100 x 50	brindle, burnt ochre, red, scottish heather, grey, buff, charcoal, bracken	11.52	1.92	576	50	1,400	253.44
rectangular 60mm	200 x 100 x 60	brindle, burnt ochre, red, grey, charcoal,	9.6	1.6	480	50	1,400	211.2
rectangular 80mm	200 x 100 x 80	brindle, burnt ochre, red, grey, charcoal	7.68	1.28	384	50	1,500	153.6

Non stock item colours can be made to order based on minimum quantities and agreement by sales team.

Visit www.lairdbros.co.uk or call us on 01307 466577