

Product Datasheet PROPERM PERMEABLE PAVING

Properm Rectangular

- Iconic shape of Properm Rectangular permeable paving creates small gaps between the blocks which allows surface water to drain
- Rectangular profile allows for distinct patterns including herringbone, stretcher bond and basket weave
- Suitable for permeable pavements, low speed roads, car parks, driveways, footpaths, heavy industrial traffic (80mm), government/council projects and road infrastructure.

Properm 240

- Extremely tough with ability of withstand heavy trafficking
- · Aesthetically stylish and permeable
- 80mm depth
- The classic and sophisticated design is ideal for providing permeable paved access for motor vehicles, children's toys with wheels, prams, roller blades, wheelchairs as its mini-chamfer virtually eliminates bumps

Properm Cobble

- Designed to create a vintage chic distressed aged look, our Properm Cobble permeable block paving is a perfect fit for those who desire to create an authentic appearance whilst controlling storm water to mitigate risk of flooding which laid with the correct SuDs system.
- 80mm depth
- The single piece tumbled Properm Cobble allows fast laying rates and interesting patterning provides the eye-catching SuDs solution for exclusive developments in both public and private surroundings

Laird Properm Ranges

- Superb colour definition with German (Lanxess) iron oxide long lasting pigments
- Enhanced durability utilising the most modern German manufacturing technology
- Reduced efflorescence
- Product manufactured by a Scottish independent, manufacturing and quarrying in Scotland, negating shipping and reducing road miles, making the actual carbon footprint incomparably lower than alternatives.

Product type	Concrete Paving Block
Manufacturing process	Hydraulically pressed
Manufactured to	BS EN 1338:2003
Installed to	BS 7533-3:2005
Strength	>3.6MPa
Slip/Skid resistance	>70 USRV (extremely low)
Chamfer	Pencil line chamfer
Surface layer	Higher intensity of pigment and cement on the wearing course
Efflorescence	Products placed in a climate controlled curing chamber to minimise its occurrence & severity
Recyclable	100% can be recycled
Application	Domestic, commercial & industrial

		colours	m2/pac	m2/slic	no./pac	no./m	weight/pack	m2/artic
product	size (mm)	manufactured	k	е	k	2	(kg)	delivery
		brindle, burnt						
	200 x 100 x	ochre, red, grey,						
Properm Rectangular 60	60	charcoal	9.6	1.6	480	50	1,300	201.80
		brindle, burnt						
	200 x 100 x	ochre, red, grey,						
Properm Rectangular 80	80	charcoal	7.68	1.28	384	50	1,390	153.60
		same as strathmore						
	240 x 160 x	colour range all						
Properm 240	80	made to order	7.68	1.53	200	26	1,390	153.60
		same as cobble						
	240 x 160 x	colour range all						
Properm Cobble	80	made to order	7.68	1.53	200	26	1,390	153.60

Non stock item colours can be made to order based on minimum quantities and agreement by sales team